


CAMLOCK COUPLING

快速接头


- 材 料: CF8M, CF8, CF3M
- 工作压力: 150Lb
- 适用温度范围: -20°C~120°C
- 螺纹类型: ISO, BS, DIN, JIS, ASME




TYPE: A




TYPE: B




TYPE: C




TYPE: D




TYPE: E




TYPE: F



TYPE: DC



TYPE: DP



- Material: CF8M, CF8, CF3M
- Working Pressure: 150Lb
- Temperature Range: -20°C~120°C
- Thread: ISO, BS, DIN, JIS, ASME

TYPE: A

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	17	21	25	30	37.5	47	59	76	102	123	151
B	37	38	43	51	54	59	75	70	70	85	85
C	32	32	38	47	55	65.5	82	96	123	152	182

TYPE: B

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	51	46	53	66	73	80	82	87	100	104	114
B	29	31	36	44	49	53	54	55	57	57	70
C	41	40	46	56	64	75	88	105	132	132	198

TYPE: C

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	13	13	19	26	32.5	45	55	69	92	115	140
B	19	19	24	31	37	50	63	75	102	127	153
C	88	88	100	104	116	132	132	161	171	187	213
D	29	29	37	45	46	50	54	58.5	58	61	70
E	41	41	46	56	65	75	88	105	133	166	198

TYPE: D

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	52	52	54	62	64	76	80	90	108	101	115
B	30	30	36	44	47	50	54	57	57	61	153
C	41	41	46	57	64	75	89	104	131	166	198

TYPE: E

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	98	98	102	114	116	133	151	162	174	190	220
B	40	40	39	46	48	53	56	59	61	68	75
C	32	32	37	46	53	63	75	92	119	146	176
D	14	14	20	26	34	43.5	56	69	95	114	140
E	18	18	25	31	38	50	63	76	104	125	153

TYPE: F

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	14	19	25	30	37	47	59	75	101	123	149
B	32	32	36	45	53	63	76	92	119	146	176
C	57	58	59	71	74	83	87	104	108	116	129

TYPE: DC

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	40	40	49	58	68	65	69	70	76	78	90
B	30	30	36	45	50	52	54	57	57	58	79
C	42	42	46	56	63	75	88	103	131	159	198

TYPE: DP

DIM	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	5	6
A	32	32	37	46	54	63	76	92	119	146	176
B	26	26	30	39	41	44	44	46	46	49	59
C	37	37	45	56	64	56	63	68	68	80	77